

ALPINE ATF MB 17

Low-viscosity HC synthetic automatic transmission fluid

Properties

- High fuel savings
- Excellent lubrication properties
- Outstanding thermal stability
- High stable viscosity index
- Very good shear stability
- Effective protection against wear, corrosion and foaming
- Excellent cooling properties
- Exceptional friction coefficient consistency

Use instructions

- Specially designed for use in latest Mercedes-Benz 9-speed automatic transmissions (NAG3)
- ATF MB 17 **is not suitable** for older Mercedes-Benz automatic transmissions and is **not** backward compatible with MB approvals MB 236.10, MB 236.12, MB 236.14 and MB 236.15

Observe manufacturer instructions!

Performance data

Recommendations*: MB 236.17

TYPICAL VALUES	METHOD	UNIT	ALPINE ATF MB 17
Density at 15°C	DIN 51 757	g/cm ³	0.835
Viscosity at 40°C	DIN ISO 3104	mm ² /s	17.10
Viscosity at 100°C	DIN ISO 3104	mm ² /s	4.23
Viscosity index (VI)	DIN ISO 2909	-	161
COC flash point	DIN ISO 2592	°C	190
Pour point	DIN ISO 3016	°C	-54
Colour	-	-	yellow-brown

* conforms to OEM specifications

The above values may vary within commercially accepted tolerances

September 2017