

MITANOL MB 14

HC-synthetic Automatic Transmission Fluid

Properties

- Top quality properties
- High load carrying capacity and extremely wear-reducing
- Superior friction value consistency
- No foam formation
- Lowest evaporation losses
- Soft switching operations even at medium temperatures
- Excellent viscosity-temperature behaviour
- Excellent oxidation and thermal stability
- Neutral towards common sealing materials

Application notes

- Especially for the new Mercedes-Benz 7-speed automatic transmission type 722.9, except code A89 and 5-speed automatic transmission with controlled torque converter lock-up clutch (KÜB) for vehicles with rear-wheel drive (722.6) **MITANOL MB 14** is downwards compatible with the previous Mercedes-Benz 4- and 5-speed passenger cars automatic transmissions (722.3, 722.4, 722.5), except the 5-speed CVT-automatic transmission (722.7).

Observe manufacturer's instructions!

Service description

Recommendation*:

- MB 236.14

TYPICAL PARAMETERS	METHODS	UNITS	MITANOL MB 14
Thickness at 15°C	DIN EN ISO 12185	kg/m ³	849
Viscosity 40°C	DIN 51 562	mm ² /s	29
Viscosity 100°C	DIN 51 562	mm ² /s	6.0
Viscosity index (VI)	DIN ISO 2909	-	164
Pour point	ASTM D 7346	°C	-51
Flash point COC	DIN ISO 2592	°C	233
Colour	-	-	red

October 2020

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.