

ALPINE® Racing 2-T

Fully synthetic two-stroke engine oil (low smoke)

Properties

- Fully synthetic two-stroke engine oil
- Excellent protection against rust, corrosion and wear
- Stable lubricating film prevents piston jamming and seizing
- Reduces deposits on piston rings, exhaust ports and spark plugs
- Offers protection against deposits and plug bridging
- Use in systems with separate and mixed lubrication
- Environmentally friendly due to low smoke emission

Application notes

ALPINE Racing 2-T is a fully synthetic two-stroke engine oil with a low-ash additive composition for sporty air and water-cooled two-stroke engines in motor vehicles, motorcycles, scooters and mopeds with separate or mixed lubrication, up to a mixing ratio of 1:50.

Observe manufacturer's instructions.

Service description

Specifications:

- API TC (TSC-3)
- ISO-L-EGD (low smoke)
- JASO FC/FD
- TISI

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE Racing 2-T
Density at 15°C	ASTM D7042	kg/m ³	870
Viscosity at 40°C	ASTM D7042	mm ² /s	72,6
Pour point	DIN EN ISO 3016	°C	-29
Flash point COC	DIN EN ISO 2592	°C	138

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.