

ALPINE Mehrzweckfett 2

Multi-purpose lithium grease

Properties

- Mixable with most conventional soap base grease products.
- Good adhesive properties.
- Shear-proof and oxidation-resistant.
- Wear reducing.
- Water resistant.
- Prevents corrosion.

Use instructions

Alpine Mehrzweckfett 2 is particularly suitable for the lubrication of all types of anti-friction and plain bearings under normal load as well as joints operated at normal temperatures and conditions. This makes it a universal lubricant for automotive vehicles, construction machines and agricultural machinery.

When re-lubricating parts, ensure that the grease is not contaminated with dust or dirt particles.

Observe manufacturer instructions.

Performance data

Specifications:

DIN 51 502: K2K-30

TYPICAL VALUES	METHOD	UNIT	ALPINE Mehrzweckfett 2
NLGI grade	ASTM D 217	-	2
Soap/thickener		-	lithium soap
Colour	visual	-	yellow brown
Texture	visual	-	smooth
Operating temperature range		°C	-30 to 120
Short term		°C	to 130
Penetration at 25°C	ISO 2137	0.1 mm	265-295
EMCOR test	ISO 11007	Rating	1
Drop point	IP396	°C	>180
Viscosity (base oil) at 40°C	ASTM D 217	mm²/s	110

The above values may vary within commercially accepted tolerances

Juni 2016