

ALPINE Special V 0W-30

Synthetic high-performance low-friction engine oil for Volvo passenger car engines

Properties

Alpine Special V 0W-30 is a synthetic high-performance low-friction oil. Its low HTHS viscosity helps reduce fuel consumption during the cold start phase and in short-distance travel.
 Guarantees optimum wear protection and great engine cleanliness.
 The product is recommended for use in Volvo passenger cars with modern, high-efficiency Euro 4, 5 or 6 engines, with or without turbocharger, direct injection, multi-valve or hybrid technology.
Alpine Special V 0W-30 helps save fuel and reduces CO₂ emissions, thus protecting the environment.

Use instructions

Alpine Special V 0W-30 with VOLVO VCC 95200377 approval is the prescribed product for petrol and diesel engines of the B5, B6, B8 and D5 series built after 2004 as well as for hybrid PHEV drives.

Performance data

Specifications: ACEA A5-/B5-12
 API SL

Recommendation*: VOLVO VCC 95200377

TYPICAL VALUES	METHOD	UNIT	ALPINE Special V 0W-30
SAE class	DIN 51 511	-	0W-30
Density at 15°C	DIN 51 757	g/cm ³	0.850
Dynam. viscosity at -35°C	DIN 51 377	mPa s	6440
Viscosity at 40°C	DIN 51 562	mm ² /s	41
Viscosity at 100°C	DIN 51 562	mm ² /s	7.9
Viscosity index (VI)	DIN ISO 2909	-	169
COC flash point	DIN ISO 2592	°C	228
Pour point	DIN ISO 3016	°C	- 39

* meets the requirements of the OEM manufacturer

The above values may vary within commercially accepted tolerances

August 2017