

XTS 0W20

DESCRIPTION

New generation fully synthetic engine oil, developed to ensure a clean engine.

APPLICATION

Bardahl XTS 0w20 improves fuel economy, increases piston cleanliness, reduces emissions, and protects against wear and the formation of muds. It can be used in turbo-charged hybrid-petrol engines. It is compatible with E85 fuel. Bardahl XTS 0w20 is suitable for modern hybrid vehicles.

SPECIFICATIONS

This product offers the following performance level:

ILSAC	GF-6A
API	SP Resource Conservering
GM	Dexos 1 Gen 2
CHRYSLER	MS 6395
FORD	WSS-M2C947-A/B1 WSS-M2C962-A1

PROPERTIES

- ✓ Offers a stable viscosity and a high viscosity index,
- ✓ Provides a good resistance against « shearing »,
- ✓ Makes cold start easier,
- ✓ Limits fuel overconsumption,
- ✓ Offers an excellent resistance against oxidation,
- ✓ Leaves a lubricating film preserved at high temperature,
- ✓ Has excellent dispersion and cleaning properties.





TECHNICAL DATA

Density at 20°C	Kg/I	0,843
Viscosity dynamic CCS	сР	4940
Viscosity at 40°C	mm2/s	44
Viscosity at 100°C	mm2/s	8,6
Viscosity Index		178
Flash point COC, °C	°C	222
Pour point, °C	°C	-36
TBN alcalinity	mgKOH/g	8,5
Sulfated ash contents	%	0,89

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMANDATIONS

<u>Handling</u>: any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

<u>Storage</u>: it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36331	12 x 1L
36333	3 x 5L
36338	20 L
36334	60 L
36337	205 L

