

ALPINE RSi 5W-30

HC-Synthetic high-performance low-friction engine oil for passenger cars

Eigenschaften

Alpine RSi 5W-30 is a HC-synthetic high-performance engine oil of SAE class 5W-30. Synthetic components combined with carefully selected innovative additives guarantee that the product meets the latest market requirements. Thanks to the significantly improved engine oil quality of **Alpine RSi 5W-30**, it offers further enhanced wear protection and keeps the engine perfectly clean, even at extended oil change intervals. The extremely low cold viscosity of the lubricant and its reliable high-temperature viscosity properties guarantee significant reductions in fuel consumption.

Einsatzhinweise

Alpine RSi 5W-30 is the ideal high-performance low-friction engine oil for demanding engines. It is used in petrol and diesel engines in passenger cars, including models with turbocharger and direct injection. The product is recommended for all operating conditions.

Leistungsbeschreibung

Specifications / Recommendations*: ACEA A3-/B4-12
 API SL / CF
 VW 502 00 / 505 00
 MB 229.3 und 229.5
 Renault RN0700 und RN0710
 Opel GM-LL-B-025
 BMW Longlife-01

TYPICAL VALUES	METHOD	UNIT	ALPINE RSi 5W-30
Density at 15°C	DIN 51 757	kg/m ³	855
Viscosity at 100°C	DIN 51 562	mm ² /s	12,2
Viscosity index (VI)	DIN ISO 2909	-	168
Dynam. Viskos.bei -30°C	DIN 51 377	mPa.s	6250
Pourpoint	DIN ISO 3016	°C	-42
COC flash point	DIN ISO 2592	°C	236
TBN	DIN ISO 3771	mgKOH/g	10

* entspricht den Anforderungen des OEM-Herstellers

Die angegebenen Werte können im handelsüblichen Rahmen schwanken

February 2017